



ALDABRA

Our name is inspired by the Aldabra atoll, in the Seychelles.

A natural paradise far from the common routes, where life renews with every tide.



OUR HISTORY







Resin line upgrade



2004



2008



2009



2012



2015

First LED lighting fixture

Worldwide distribution





Aldabra Lighting Ltd opening


Introduction of nanopolymeric resin technology



2018



2019



2020



2022



2023

Aldabra USA opening

Aldabra Paraguay opening

20 years of Aldabra

Aldabra Middle East office opening

Lifetime warranty



VISION

Light to live, not just to see

We envision a world where light is a transformative tool that reshapes how we perceive spaces, improves liveability and sparks emotions.



MISSION


Beauty in innovation

Our mission is to seamlessly fuse the most advanced technologies with elegant, minimal design, consistently pushing the boundaries of innovation while respecting the environment. Every idea that gets into reality gives birth to a unique product, realized with extreme quality in every detail.

WORLDWIDE DISTRIBUTION



OUR BUSINESS PROCESS



PRODUCTION







Prototyping R&D Machining Nanopolymeric Resin Plating
Professional Equipment
Assembly

Aquastop
Design
Made in Italy



SUPPLIERS

We uphold our quality standards by exclusively procuring components from **premium suppliers**.

This **meticulous selection** ensures that every facet of our products embodies the **excellence** that defines our brand.









TCI Leds

Bridgelux

Seoul Semiconductors Samsung







Ledil

Citizen

Lumileds

WORLD LEADING QUALITY



5 YEARS
STANDARD WARRANTY
ON ALL PRODUCTS



LIFETIME
WARRANTY ON WATER
RESISTANCE

STORM COLLECTION





STORM COLLECTION









X-Treme 22



Ek 1



Ek 2



Ek 3



Ek 4



Vitro



Vertebra



Miniver



Flexi Top



Flexi Side



Filo



Linea



Traccia



Azimut



Star



Punto



Eclips



Stecco 15




Monolite

VERTEBRA SERIES











Professional flexible lighting system with power LEDs and optics

- · Wall grazer for curved surfaces, facades, columns
- · Extremely clean design, minimal visual impact
- · Suitable for indoor and outdoor applications
- · Fully made of nanopolimeric resin, UV resistant



VERTEBRA

Light Source & Power Supply



118 - 130 Im/W

9 - 18 - 36 W

costant voltage 24 Vdc

Optics







LED Colors





3000 K

Materials

Finishes



Alluminium








Transparent

Technical drawings





Functions



dimmable

Installations

surface mounted















Light Source & Power Supply



140 - 180 Im/W 22 W/m costant voltage 24 Vdc

Optics







LED Colors






Materials







Technical drawings



(0.59°)

Functions



Installations


surface mounted













Professional side or top bendable lighting fixture

- · Signal lighting for curved surfaces facades, columns
- · Suitable for indoor, outdoor and underwater applications
- · Superior material and finish quality
- · Fully made of nanopolimeric resin, UV resistant




Light Source & Power Supply




80 - 100 lm/W 10 - 19 W/m

Optics



LED Colors




Materials

Resin



Technical drawings



Maximum length 5 m (197")

Functions



Installations



Finishes















FLEXI SIDE

Light Source & Power Supply



80 - 100 Im/W

10 - 19 W/m

costant voltage 24 Vdc

Optics



LED Colors




Materials

Resin



Finishes

Technical drawings



Maximum length 5 m (197")

Functions



Installations



























Professional modular linear lighting systems for signal lighting

- · Resin-covered electronics for complete impermeability
- · Suitable for indoor, outdoor and underwater applications
- · Corners and edges in single piece, with perfect light continuity
- · Possibility of graphical personalization (EK3 and EK4)
- Premium materials and glass-like finish, available also in stainless steel 316L (EK1 and EK2)



EK 1

Light Source & Power Supply




140 - 180 Im/W

8 - 15 W/m

costant voltage 24 Vdc

Optics



LED Colors



Materials







Steel



Finishes



Technical drawings

46,5 (1,83")



Stainless steel

(0,59")



Aluminium

(0,61")

Functions



dimmable

Installations

recessed with housing





















Light Source & Power Supply



140 - 180 Im/W

12 - 15 W/m

costant voltage 24 Vdc

Optics



LED Colors



Materials








Finishes



Technical drawings



Functions



Installations

recessed with housing



















EK 3

Technical drawings



Light Source & Power Supply




140 - 180 Im/W

12 - 15 W/m

costant voltage 24 Vdc

(1,574") 40 (1,574")

Optics







Functions



dimmable

LED Colors



Installations



Materials



Finishes



























Technical drawings



Light Source & Power Supply

140 - 180 Im/W

36 W/m

voltage 24 Vdc

80 (3,149") 40 (1,574")





Functions



dimmable

LED Colors







Installations

recessed with housing

Materials



Alluminium



Finishes















































Professional lighting system for wall grazing

- · Resin-covered electronics for complete impermeability
- · Lens protection for no light flux distortion
- · No weak points against water resistance
- · Suitable for indoor and outdoor applications
- · Glass-like finish



X-TREME 22

Light Source & Power Supply



Optics

105 - 130 Im/W

20 W/m

costant voltage 24 Vdc


elliptical

voltage 110 - 240 Vac

Technical drawings

23,5 (1,787")





Functions



dimmable

LED Colors







Materials



Stainless Alluminium Steel 316L



Resin

Finishes



Stainless

Steel



Anodized Alluminium

Installations

surface mounted















X-TREME 35

Light Source & Power Supply



105 - 130 Im/W 30 W/m

costant voltage 24 Vdc mains voltage 110 - 240 Vac

Optics









LED Colors











Satin

Stainless

Steel

Materials



Anodized Stainless Alluminium Steel 316L




Resin



Finishes

Anodized Alluminium

Technical drawings



Functions



Installations

surface mounted



















Professional linear lighting system for direct and indirect lighting

- · Premium materials
- · Extremely compact system
- · Suitable for indoor, outdoor and underwater applications
- · Double protection for watertight seal: resin-covered electronics and sealed polycarbonate cover tube







Light Source & Power Supply



140 - 180 Im/W

8 - 24 W/m

voltage 24 Vdc



Optics



transparent

Functions



dimmable

LED Colors



Finishes

Installations


surface mounted

Materials



Alluminium Steel 316L

Stainless





























Professional linear lighting system for direct and indirect lighting

- · Resin-covered electronics for complete impermeability
- · Minimum encumbrance for an impermeable product
- · Ideal for narrow spaces, niches, steps, cornices
- · Glass-like finish



Technical drawings



Light Source & Power Supply



105 - 130 Im/W

12 - 24 W/m

costant voltage 24 Vdc

16,5 (0,649")

Optics



transparent

Functions



dimmable

LED Colors





Installations

surface mounted

Materials



Finishes

















LINEA







Professional recessed lighting system for walls and ceilings

- · Symmetric and asymmetric optics
- · Resin-covered electronics for complete impermeability
- · Minimum recessed depth
- · Glass-like finish



Technical drawings



Light Source & Power Supply




140 - 180 Im/W

25 - 40 W/m

costant voltage 24 Vdc

voltage 110 - 240 Vac

Symmetric (1,968")



Optics



Functions



LED Colors





Installations

recessed with housing

recessed with springs

Materials





























TRACCIA

Professional linear signal system for stairs, sidewalks and corners

- · Resin-covered electronics for complete impermeability and increased mechanical resistance
- · Suitable for stairs, sidewalks and corners
- · Possibility of both direct and indirect lighting
- · Anti-slip rubber incorporated

TRACCIA

Technical drawings



Light Source & Power Supply




140 - 180 Im/W

18 W/m costant voltage 24 Vdc

86 (3,385") 21 (0,826")

Optics



Functions



LED Colors



Installations

surface mounted

Materials







Rubber

Finishes



Certifications




P67





















Professional recessed fixture for grounds or walls



- · Version with minimum recessed depth
- · High variety of light beams and optics
- · Anti-vandal screws for fixture protection
- · Premium materials: aluminum, stainless stees 316L and tempered glass





STAR

Light Source & Power Supply



Power LED 125 Im/W

COB LED 145 Im/W

13 - 18 W

costant voltage 24 Vdc

voltage 110-277 mΑ

current 350/500

Technical drawings



Star 120

Star 120 compact





Optics









Vac

honeycomb

Functions



LED Colors



Alluminium





Installations

recessed with housing

Materials



Stainless

Steel



Tempered Glass

Finishes Certifications



Satin

Stainless

Steel
















PUNTO








PUNTO

Professional recessed spotlight for signal lighting



- · Suitable for indoor, outdoor and underwater applications
- · Resin-covered electronics for complete impermeability
- · Premium material, stainless steel 316L
- · Extremely compact dimensions

PUNTO

Technical drawings



Light Source & Power Supply




140 - 180 Im/W

0,5 W

voltage 24 Vdc



Optics



Functions



LED Colors











Installations

recessed with housing

Materials



Finishes































Professional floodlight for direct and indirect lighting

- · Wall, floor or ceiling surface mounted with integrated adjustable bracket
- · Perfect for lighting monuments, facades, columns, showcases and gardens
- · Compact dimension and optimal visual comfort
- · Available in three dimensions with high variety of optics
- · Resin-covered electronics for complete impermeability



AZIMUT

Technical drawings



Light Source & Power Supply



110 - 145 Im/W

3 - 22 W

voltage 24 Vdc

voltage 110 - 240 Vac

Azimut 48



Azimut 58



Azimut 95

115 (4,528")

Optics









Functions



surface mounted dimmable

LED Colors

Materials



Steel 316L



Alluminium

alloy



Finishes



Sablè





Sablè



Certifications

Installations












ECLIPS SERIES







ECLIPS

Recessed fixture with asymmetric light beam for signal lighting

- · Visual comfort, recessed optics and no visible
- · Resin-covered electronics for complete impermeability
- · Available in three shapers: rectangular, square and circular
- · Suitable for indoor and outdoor applications

ECLIPS

Technical drawings



Light Source & Power Supply



105 - 130 Im/W

1 - 4 W

current 350/500 mΑ

Eclips 30

Eclips R 28 (1,102")

28 (1,102")

Eclips Q

28 (1,102")



Optics



Asymmetric

Functions



dimmable

LED Colors







Materials









Finishes

Installations















STECCO SERIES









Professional exterior bollard family in aluminium and resin

- · Available with mono-directional or bi-directional light
- · Resin-covered electronics for complete impermeability and increased resistance
- · Minimal design, available in two versions: straight and inclined
- · Power supply included in the fixture



STECCO

Technical drawings

Stecco 15S



Light Source & Power Supply



140 - 180 Im/W

15 - 60 W

voltage 110 - 264 Vac

09 38 (1,496°) (5,905°)

Stecco 15

Optics



opal

Functions



LED Colors





3300 K 5200 K

Installations



Materials























MONOLITE SERIES









Aluminium and resin bollards family with diffusive homogeneous light emission

- · Available with mono-directional or bi-directional light
- · Resin-covered electronics and insets for complete impermeability and increased resistance
- · Symmetric emission with incorporated decorative
- · Asymmetric emission with incorporated louver



MONOLITE

Technical drawings

174 (6,85")



Light Source & Power Supply




140 - 180 Im/W 20 - 80 W voltage 110-277 Vac

Functions



96,5 (3,799")

Optics



LED Colors







Installations

surface mounted

Materials



Finishes









BEST SELLER INTERIOR



BEST SELLER INTERIOR









Innovative modular linear LED lighting system mounted on suspended electrified cables or bars

- · Direct or indirect dimmable emission, visual comfort and anti-glare system
- · It allows the creation of the desired shape directly on place, and shapes can be changed with minimum effort.
- · Perfect solution for large spaces: museums, offices, houses, lobbies, halls, libraries, churches, lighting of frescoed or wooden ceilings
- · Horizontal or vertical cables with wall/wall wall/ ceiling ceiling/floor fixing or rigid bars suspended from the ceiling





Light Source & Power Supply




90 - 110 Im/W

130 Im/W 120 - 130 Im/W

voltage 24 Vdc

Technical drawings



Optics







dimmable OFF

Functions

LED Colors







Materials



Anodized Alluminium Alluminium





Alluminium





Installations

supported on cables or rigid bars

ON

Finishes













SHANGHAI



Innovative suspended linear LED lighting system for ceilings

- · Wireless connection between modules
- · It allows the creation of infinite combinations and shapes directly on place
- · Direct or indirect lighting
- · Reduced usage of power supply cables and suspension cables for extreme ceiling cleanness



SHANGHAI

Technical drawings

Light Source & Power Supply



140 - 180 Im/W

voltage 24 Vdc

Optics



satin diffuser

Functions



LED Colors



Alluminium





Installations



Materials











Finishes



















Indoor skirting board with uniform indirect light for floors or ceiling lighting

- · Surface mounted or recessed versions available
- · Extreme visual comfort
- · Inspectable electronics to allow maintenance without moving the fixture
- · Can be cut on the worksite as common skirting boards







Light Source & Power Supply

140 - 180 Im/W

Optics



diffuser

LED Colors







Materials




Finishes






Technical drawings







Functions



dimmable

Installations

surface mounted


recessed












HOLE



HOLE



Trimless recessed spot light for interiors with recessing box

- · Anti-glare rearward optic
- · Minimal and clean design
- · The spot-light is hold by a magnet and can be easily removed for easy maintenance
- · Fixture can be mounted in the recessing box after ceiling completion and can be easily removed



Light Source & Power Supply




140 - 180 Im/W

105 - 130 Im/W

costant voltage 24 Vdc

constant current 350 mA

Technical drawings





Optics



transarent diffuser



LED Colors







Functions



dimmable

Installations

ceiling recessed

Materials



Stainless Alluminium Steel 316L alloy



PMMA

Finishes











COMING SOON OUR NEXT PRODUCTS

Innovation & Design

A new way of lighting outdoor spaces


TRAMA



Power: 15W







Power: 26-50W




ECLIPS P



Power: 1,5W



SEGNO



Power: 5-15W





THANK YOU